



Tech Info Library

Apple III: Cables for Various Printers (2 of 4)

Revised: 11/19/86
Security: Everyone

Apple III: Cables for Various Printers (2 of 4)

=====

Apple III Drivers Aid Cable "C"

Device Manufacturer and Models:

Diablo	620
Diablo	630 (Use as shown; DO NOT change pin 20!)
Diablo	1630
Diablo	1640
Diablo	1650
Xerox	630 (See change; this model ONLY; re: pin 20)
Xerox	1710
Xerox	1720
Xerox	1730
Xerox	1741
Xerox	1750

Pin-to-Pin Connections:

Apple III (Male) Diablo or Xerox (usually Female)

1	o-----o	1
2	o-----o	3
4	o-----+---o	6
		+---o 8
6	o-----o	20 (on Xerox 630 ONLY
		go to pin 11
		instead of pin 20)
7	o-----o	7
		+---o 4
		+---o 5

Wiring Comments:

Apple III pin 4	Tie device pins
tie to device pins	6 + 8 together
6 + 8	
	Tie device pins

4 + 5 together; they do
not connect to the Apple III

Change pin 20 to pin 11
ONLY for the Xerox 630!

Note: For proper operation when using the Apple III Super Serial Card (Apple P/N A2B0044) in an Apple III make sure that switch SW 2-6 (on the card) is in the "ON" position and that the jumper block (also on the card) is in the "TERMINAL" Position.

Apple III Drivers Aid Cable "D"

Device Manufacturer and Model:

Texas Instruments 810
Centronics 737

Pin-to-Pin Connections:

Apple III (Male) Texas Instruments (usually Female)

1	o-----o	1
2	o-----o	3
4	o-----+---o	6
		+---o 8
6	o-----o	11
7	o-----o	7

Wiring Comments:

Apple III pin 4	Tie device pins
tie to device pins	6 + 8 together
6 + 8	

Note: For proper operation when using the Apple III Super Serial Card (Apple P/N A2B0044) in an Apple III make sure that switch SW 2-6 (on the card) is in the "ON" position and that the jumper block (also on the card) is in the "TERMINAL" Position.

Apple III Drivers Aid Cable "E"

Device Manufacturer and Models:

Okidata 82A
Okidata 83A

Pin-to-Pin Connections:

Apple III (Male) Okidata (usually Female)

1	o-----o	1
---	---------	---

```

2  o-----o 3
7  o-----o 7
20 o-----o 11
      +---o 6
      +---o 20

```

Wiring Comments:

```

Tie device pins
6 + 20 together; they do
not connect to the Apple III

```

Note: For proper operation when using the Apple III Super Serial Card (Apple P/N A2B0044) in an Apple III make sure that switch SW 2-6 (on the card) is in the "ON" position and that the jumper block (also on the card) is in the "TERMINAL" Position. Apple III Drivers Aid Cable "F" description on next record.

Apple Technical Communications

Tech Info Library Article Number:293