



Tech Info Library

Super Serial Card: Cable for TI 810 Printer (11/96)

Revised: 11/21/96
Security: Everyone

Super Serial Card: Cable for TI 810 Printer (11/96)

Article Created: 04 December 1984
Article Reviewed/Updated: 21 November 1996

TOPIC -----

Listed below are the cable pinouts for connecting the Super Serial card to a TI 810 printer.

DISCUSSION -----

Super Serial Card (SSC)	Pin	Cable	Pin	Printer Connector
Frame Ground	(FG)..... 1	<----->	1.....	(FG)
Transmit Data	(Tx) 2	<----->	3.....	(Rx)
Receive Data	(Rx) 3			
Request to send	(RTS) 4			
Clear To Send	(CTS) 5			
Data Set Ready	(DSR) 6	<----->	20.....	(DTR)
Signal Ground	(SG)..... 7	<----->	7.....	(SG)
Data Carrier Detect	(DCD) 8			
Secondary Clear To Send	(SCTS) ... 19			
Data Terminal Ready	(DTR) 20			

Printer settings

* 1200 baud, Odd Parity, 7 Data Bits and 1 Stop Bit.

* Jumper Pins 6, 8, and 9 together on the printer but not connect them to the Super Serial card.

* Switch 1 2 3 4 5 6 7 (The switch is located inside the access cover.)
1 1 0 1 1 1 1

Super Serial card settings

Switch Settings: 1 = On = Closed; 0 = Off = Open

Switch	1	2	3	4	5	6	7
SW1:	0	1	1	1	1	1	1
SW2:	1	0	1	0	1	0	0

Article Change History:

21 Nov1996 - Reviewed for technical accuracy, revised formatting.

Copyright 1984-96, Apple Computer, Inc.

Tech Info Library Article Number:943